

Description

Thread Size: 3/16", Nut Length: 15/16", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS680A3K |
| Minimum Qty (MOQ): | 50 EA |
| NSN: | 5310-00-655-5889 |
| Schedule B: | 9401.90.5081 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS680A3K Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.948 Inches Nominal |
| Nut Height: | 0.250 Inches Nominal |
| Plate Thickness: | 0.047 Inches Nominal |
| Plate Width: | 0.328 Inches Nominal |
| Nut Mounting Provision: | Countersunk Holes |
| Mounting Provision Location: | Nut Projection Side |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.344 Inches Nominal |
| Center To Center Distance Between Mounting Holes Along Length: | 0.686 Inches Minimum And 0.690 Inches Maximum |
| Temp Rating: | 550.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.190 Inches |
| Mounting Hole Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 80205-nas 680a3k Professional/industrial Association Standard |

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS680A3K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.