

## **P/N NAS680A6**

## **Description**

Thread Size: 3/8", Nut Length: 1-9/32", Nut Height: 11/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS680A6

Minimum Qty (MOQ): 15 EA

NSN: 5310-00-616-8897

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS680A6 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.130 Inches Nominal
Nut Style:	Plate
Nut Length:	1.292 Inches Nominal
Nut Height:	0.344 Inches Nominal
Plate Thickness:	0.075 Inches Nominal
Plate Width:	0.688 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	1.000 Inches Nominal
Temp Rating:	550.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

### **How to Order**

Order this plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS680A6">https://military-fasteners.com/nuts/locknuts/NAS680A6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.