

# P/N NAS680C4

Military-Fasteners.com

#### Description

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 9/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	NAS680C4
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-680-6518
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated



## P/N NAS680C4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	1.260 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Plate Width:	0.414 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	1.000 Inches Nominal
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall

### **How to Order**

Order this plate - two lug locknut from our inventory online by visiting <u>https://military-fasteners.com/nuts/locknuts/NAS680C4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.