

**Description**

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | NAS680C4                                 |
| Minimum Qty (MOQ):      | 15 EA                                    |
| NSN:                    | 5310-00-680-6518                         |
| Schedule B:             | 7318.16.0085                             |
| ECCN:                   | EAR99                                    |
| National Motor Freight: | 093480, Bolts / Nuts Metal Silver Plated |

NO IMAGE  
AVAILABLE

## P/N NAS680C4 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3b   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design                 |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum      |
| <b>Nut Style:</b>   | Plate  |
| <b>Nut Length:</b>  | 1.260 Inches Maximum                               |
| <b>Nut Height:</b>  | 0.281 Inches Maximum                               |
| <b>Plate Thickness:</b>   | 0.055 Inches Maximum                               |
| <b>Plate Width:</b>   | 0.414 Inches Maximum                               |
| <b>Nut Mounting Provision:</b>  | Straight Holes                                     |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes  |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.500 Inches Nominal                               |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 1.000 Inches Nominal                               |
| <b>Temp Rating:</b>   | 800.0 Deg Fahrenheit Nominal                       |
| <b>Thread Series:</b>   | Unf  |
| <b>Thread Quantity Per Inch:</b>                                      | 28   |
| <b>Nominal Thread Size:</b>   | 0.250 Inches                                       |
| <b>Material:</b>  | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>                          | Ams 5525 Assn Std Single Material Response Overall |
| <b>Precious Material:</b>   | Silver   |
| <b>Surface Treatment:</b>   | Silver Overall                                     |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS680C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.