

Description

Thread Size: 3/8", Nut Length: 1-9/32", Nut Height: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS680X6
Minimum Qty (MOQ):	20 EA
NSN:	5310-00-262-0937
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS680X6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.379 Inches Minimum Nut
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.344 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.500 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas680 Professional/industrial Association Standard

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS680X6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.