

Description

Fastener Length: 2-7/32", Thread: 5/8-18, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6810DU21 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-457-9429 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS6810DU21 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.877 Inches Minimum And 0.927 Inches Maximum |
| Fastener Length: | 2.199 Inches Minimum And 2.229 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.312 Inches Minimum And 0.327 Inches Maximum |
| Width Between Flats: | 0.928 Inches Minimum And 0.940 Inches Maximum |
| Grip Diameter: | 0.6235 Inches Minimum And 0.6240 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.625 Inches |
| Grip Length: | 1.312 Inches Minimum And 1.322 Inches Maximum |
| Thread Quantity Per Inch: | 18 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.965 Inches Nominal First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6810 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6810DU21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.