

Description

Thread Size: 19/64", Nut Length: 1-13/64", Nut Height: 21/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS682A5 |
| Minimum Qty (MOQ): | 15 |
| NSN: | 5310-00-754-3206 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS682A5 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Mounting Hole Diameter: | 0.130 Inches Minimum And 0.135 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 1.210 Inches Maximum |
| Nut Height: | 0.328 Inches Maximum |
| Plate Width: | 0.505 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.495 Inches Minimum And 0.505 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.310 Inches Minimum And 0.314 Inches Maximum |
| Temp Rating: | 550.0 Deg Fahrenheit Nominal |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS682A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.