

## **P/N NAS686C08M**

### **Description**

Thread Size: 5/32", Nut Length: 15/16", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS686C08M

Minimum Qty (MOQ): 20 EA

NSN: 5310-00-820-6767

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS686C08M Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.168 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.416 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.344 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Specification/standard Data:	80205-nas686 Professional/industrial Association Standard

## **How to Order**

Order this plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS686C08M">https://military-fasteners.com/nuts/locknuts/NAS686C08M</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.