



Military-Fasteners.com

P/N NAS686C5M

Description


Thread Size: 19/64", Nut Length: 1-9/32", Nut Height: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS686C5M
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-779-6636
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS686C5M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.292 Inches Maximum
Nut Height:	0.328 Inches Maximum
Plate Thickness:	0.045 Inches Maximum
Plate Width:	0.412 Inches Minimum And 0.609 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.998 Inches Minimum And 1.002 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS686C5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.