

Description

Thread Size: 19/64", Nut Length: 1-9/32", Nut Height: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS686C5M |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5310-00-779-6636 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS686C5M Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.130 Inches Minimum And 0.135 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 1.292 Inches Maximum |
| Nut Height: | 0.328 Inches Maximum |
| Plate Thickness: | 0.045 Inches Maximum |
| Plate Width: | 0.412 Inches Minimum And 0.609 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.495 Inches Minimum And 0.505 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.998 Inches Minimum And 1.002 Inches Maximum |
| Temp Rating: | 450.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS686C5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.