

Description

Thread Size: 1/4", Nut Length: 1", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS686X3
Minimum Qty (MOQ):	45 EA
NSN:	5310-00-778-2655
Schedule B:	7318.16.0085
ECCN:	9A991.
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS686X3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Soluble Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.948 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.032 Inches Maximum
Plate Width:	0.290 Inches Minimum And 0.416 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.339 Inches Minimum And 0.349 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.686 Inches Minimum And 0.690 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall

How to Order

Order this plate self-locking nut from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS686X3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.