

**Description**

Thread Size: 5/32", Nut Length: 1-3/64", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS687C08M
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-841-1195
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS687C08M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Nominal Mils And 0.103 Nominal Centimeters
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	1.051 Inches Maximum
<b>Nut Height:</b>	0.250 Nominal Centimeters
<b>Plate Thickness:</b>	0.032 Nominal Centimeters
<b>Plate Width:</b>	0.422 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.339 Inches Minimum And 0.349 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.310 Inches Minimum And 0.314 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Features Provided:</b>	Floating Nut
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Specification/standard Data:</b>	80205-nas687 Professional/Industrial Association Standard

## How to Order

Order this plate - one lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS687C08M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.