

## **P/N NAS696A04**

### **Description**

NAS696A04 Self-Locking Nutplate

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS696A04
Minimum Qty (MOQ): 25

NSN: 5310-00-655-5880

Schedule B: 7318.16.0000

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS696A04 Specifications**

Thread Class: 3b	
Thread Direction: Right-hand	
Locking Feature: Prevailing Torque All Metal Design	
<b>Lubrication:</b> Dry Film Lubricant	
Mounting Hole Diameter: 0.066 Inches Minimum And 0.071 Inches Maximum	
Nut Style: Plate	
Nut Length: 0.550 Inches Maximum	
Nut Height: 0.143 Inches Maximum	
Plate Thickness: 0.040 Inches Maximum	
Plate Width: 0.194 Inches Maximum	
Nut Mounting Provision: Straight Holes	
Mounting Hole Arrangement Style: 2 Holes	
Distance From Aperture Center To Mounting Hole Center: 0.143 Inches Minimum And 0.153 Inches Maximum	
Center To Center Distance Between Mounting Holes Along Length:  0.217 Inches Minimum And 0.221 Inches Maximum	
Temp Rating: 450.0 Deg Fahrenheit Nominal	
Thread Series: Unjc	
Thread Quantity Per Inch: 40	
Nominal Thread Size: 0.112 Inches	
Material: Steel Overall	
Surface Treatment: Cadmium Overall	
Surface Treatment Document And Classification:  Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall Or Qq-p-41 Treatment Response Overall	.6 Ty 2 Cl 3 Fed Spec Single

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/NAS696A04">https://military-fasteners.com/nuts/self\_locking+nutplates/NAS696A04</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.