

Description

Thread Size: 1/8", Nut Length: 43/64", Nut Height: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS696C06LMK
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-266-8294
Schedule B:	7318.16.0085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS696C06LMK Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.684 Inches Maximum
Nut Height:	0.171 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.265 Inches Maximum
Nut Mounting Provision:	Countersunk Holes Or Dimpled Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.213 Inches Minimum And 0.223 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	500.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Specification/standard Data:	80205-nas696 Professional/Industrial Association Standard

How to Order

Order this plate - one lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS696C06LMK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.