

**Description**

Thread Size: 1/8", Nut Length: 43/64", Nut Height: 5/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS696C06LMK
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-266-8294
Schedule B:	7318.16.0085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS696C06LMK Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.684 Inches Maximum
<b>Nut Height:</b>	0.171 Inches Maximum
<b>Plate Thickness:</b>	0.047 Inches Maximum
<b>Plate Width:</b>	0.265 Inches Maximum
<b>Nut Mounting Provision:</b>	Countersunk Holes Or Dimpled Holes
<b>Mounting Provision Location:</b>	Opposite Nut Projection Side
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.213 Inches Minimum And 0.223 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Temp Rating:</b>	500.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Mounting Hole Countersink Angle:</b>	98.0 Degrees Minimum And 102.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas696 Professional/Industrial Association Standard

## How to Order

Order this plate - one lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS696C06LMK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.