

P/N NAS697A3

Description

Thread Size: 3/16", Nut Length: 23/32", Nut Height: 1/4", two lug, NAS697 series nut

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS21069L3

SKU / Model: NAS697A3

Minimum Qty (MOQ): 50

NSN: 5310-00-655-5869

Schedule B: 7318.16.0085

ECCN: EAR99







^{*} See page 2 for technical characteristics

P/N NAS697A3 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.724 Inches Nominal
Nut Height:	0.250 Inches Nominal
Plate Thickness:	0.047 Inches Nominal
Plate Width:	0.328 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.250 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.498 Inches Minimum And 0.502 Inches Maximum
Temp Rating:	550.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas697 Professional/industrial Association Standard

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self-locking+nutplates/NAS697A3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/nuts/self-locking+nutplates/NAS697A3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhttps://military-fasteners.com/nuts/self-locking+nutplates/NAS697A3 and selecting the quantity