

Description

Thread Size: 19/64", Nut Length: 1", Nut Height: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS697A5
Minimum Qty (MOQ):	15 EA
NSN:	5310-00-655-5871
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS697A5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.006 Inches Nominal
Nut Height:	0.328 Inches Nominal
Plate Thickness:	0.065 Inches Nominal
Plate Width:	0.505 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.359 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.716 Inches Minimum And 0.720 Inches Maximum
Temp Rating:	550.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS697A5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.