

**Description**

Thread Size: 5/64", Nut Length: 13/32", Nut Height: 7/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS697C02M
Minimum Qty (MOQ):	5 EA
NSN:	5310-01-098-9964
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

# P/N NAS697C02M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.066 Inches Minimum And 0.071 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.410 Inches Maximum
<b>Nut Height:</b>	0.110 Inches Maximum
<b>Plate Thickness:</b>	0.035 Inches Maximum
<b>Plate Width:</b>	0.162 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.124 Inches Minimum And 0.126 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.248 Inches Minimum And 0.252 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	56
<b>Nominal Thread Size:</b>	0.086 Inches
<b>iii Part Name Assigned By Controlling Agency:</b>	Navy Special Project
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall
<b>Specification/standard Data:</b>	80205-nas697 Professional/industrial Association Standard

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS697C02M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.