

**Description**

Thread Size: 7/64", Nut Height: 1/8", Head Width: 15/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS697C04M
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-820-7014
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS697C04M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.125 Inches Maximum
<b>Width Across Flats:</b>	0.240 Inches Minimum And 0.252 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Countersink Angle:</b>	120.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS697C04M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.