

Description

Thread Size: 1/8", Nut Length: 5/8", Nut Height: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS697C06L
Minimum Qty (MOQ):	50 EA
NSN:	5310-00-843-7753
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS697C06L Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.098 Nominal Mils And 0.103 Nominal Centimeters
Nut Style:	Plate
Nut Length:	0.661 Inches Maximum
Nut Height:	0.171 Nominal Centimeters
Plate Thickness:	0.047 Nominal Centimeters
Plate Width:	0.265 Inches Maximum
Nut Mounting Provision:	Countersunk Holes
Mounting Provision Location:	Opposite Nut Projection Side
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.218 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.435 Inches Minimum And 0.439 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Mounting Hole Countersink Angle:	98.0 Degrees Minimum And 102.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall
Specification/standard Data:	80205-nas697 Professional/industrial Association Standard

How to Order

Order this nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS697C06L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.