

**Description**

Thread Size: 5/32", Nut Length: 11/16", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS697C08K                                |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5310-00-176-6566                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

# P/N NAS697C08K Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design                  |
| <b>Lubrication:</b>   | Soluble Lubricant                                   |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum       |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.692 Inches Maximum                                |
| <b>Nut Height:</b>  | 0.250 Inches Maximum                                |
| <b>Plate Thickness:</b>   | 0.047 Inches Maximum                                |
| <b>Plate Width:</b>   | 0.230 Inches Minimum And 0.297 Inches Maximum       |
| <b>Nut Mounting Provision:</b>  | Countersunk Holes                                   |
| <b>Mounting Provision Location:</b>                                   | Opposite Nut Projection Side                        |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.234 Inches Nominal                                |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.466 Inches Minimum And 0.470 Inches Maximum       |
| <b>Temp Rating:</b>   | 800.0 Deg Fahrenheit Nominal                        |
| <b>Thread Series:</b>   | Unjc  |
| <b>Thread Quantity Per Inch:</b>                                      | 32  |
| <b>Nominal Thread Size:</b>   | 0.164 Inches  |
| <b>Mounting Hole Countersink Angle:</b>                               | 98.0 Degrees Minimum And 102.0 Degrees Maximum      |
| <b>Material:</b>  | Iron Alloy 660 Overall                              |
| <b>Material Document And Classification:</b>                          | Ams 5525 Assn Std Single Material Response Overall  |
| <b>Precious Material:</b>   | Silver  |
| <b>Surface Treatment:</b>   | Silver Overall                                      |
| <b>Surface Treatment Document And Classification:</b>                 | Ams 2410 Assn Std Single Treatment Response Overall |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS697C08K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.