

# **P/N NAS697C4**

### **Description**

Thread Size: 1/4", Nut Length: 3/4", Nut Height: 1/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS697C4
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-812-3869
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS697C4 Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.254 Inches Minimum Nut
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.786 Inches Maximum
Nut Height:	0.281 Inches Maximum
Plate Thickness:	0.055 Inches Maximum
Plate Width:	0.415 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.281 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.562 Inches Nominal
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

## **How to Order**

Order this plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/locknuts/NAS697C4">https://military-fasteners.com/nuts/locknuts/NAS697C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.