

Description

Thread Size: 7/64", Nut Length: 21/64", Nut Height: 9/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS698A04 |
| Minimum Qty (MOQ): | 25 EA |
| NSN: | 5310-00-655-5852 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS698A04 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Mounting Hole Diameter: | 0.066 Inches Minimum And 0.071 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.331 Inches Nominal |
| Nut Height: | 0.143 Inches Nominal |
| Plate Thickness: | 0.040 Inches Nominal |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.143 Inches Minimum And 0.153 Inches Maximum |
| Temp Rating: | 500.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698A04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.