

Description

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS698A06 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5310-00-655-5892 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS698A06 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Mounting Hole Diameter: | 0.066 Inches Minimum And 0.071 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.379 Inches Maximum |
| Nut Height: | 0.171 Inches Maximum |
| Plate Thickness: | 0.047 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.167 Inches Minimum And 0.177 Inches Maximum |
| Temp Rating: | 500.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698A06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.