

Description

Thread Size: 5/32", Nut Length: 29/64", Nut Height: 11/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS698A08
Minimum Qty (MOQ):	50
NSN:	5310-00-559-0491
Schedule B:	7318.16.0015
ECCN:	EAR99



P/N NAS698A08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.453 Inches Nominal
Nut Height:	0.172 Inches Nominal
Plate Thickness:	0.032 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.228 Inches Minimum And 0.239 Inches Maximum
Temp Rating:	550.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698A08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.