

Description

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS698C06
Minimum Qty (MOQ):	35 EA
NSN:	5310-00-971-7548
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS698C06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Mounting Hole Diameter:	0.066 Inches Minimum And 0.071 Inches Maximum
Nut Style:	Plate
Nut Length:	0.379 Inches Maximum
Nut Height:	0.171 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.167 Inches Minimum And 0.177 Inches Maximum
Temp Rating:	800.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698C06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.