

**Description**

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS698C06M
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-060-7670
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS698C06M Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.066 Inches Minimum And 0.071 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.379 Inches Maximum
<b>Nut Height:</b>	0.171 Inches Maximum
<b>Plate Thickness:</b>	0.047 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.167 Inches Minimum And 0.177 Inches Maximum
<b>Temp Rating:</b>	500.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall
<b>Precious Material And Location:</b>	External Surfaces Silver
<b>Precious Material:</b>	Silver
<b>Surface Treatment:</b>	Silver Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2410 Assn Std Single Treatment Response Overall

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS698C06M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.