

**Description**

Thread Size: 1/8", Nut Length: 3/8", Nut Height: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS698C06M                                |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5310-00-060-7670                          |
| Schedule B:             | 7318.24.0000                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS698C06M Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>                                      | Right-hand  |
| <b>Locking Feature:</b>                                       | Prevailing Torque All Metal Design                  |
| <b>Lubrication:</b>   | Dry Film Lubricant                                  |
| <b>Mounting Hole Diameter:</b>                                | 0.066 Inches Minimum And 0.071 Inches Maximum       |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.379 Inches Maximum                                |
| <b>Nut Height:</b>  | 0.171 Inches Maximum                                |
| <b>Plate Thickness:</b>                                       | 0.047 Inches Maximum                                |
| <b>Nut Mounting Provision:</b>                                | Straight Holes                                      |
| <b>Mounting Hole Arrangement Style:</b>                       | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b> | 0.167 Inches Minimum And 0.177 Inches Maximum       |
| <b>Temp Rating:</b>   | 500.0 Deg Fahrenheit Nominal                        |
| <b>Thread Series:</b>   | Unjc  |
| <b>Thread Quantity Per Inch:</b>                              | 32  |
| <b>Nominal Thread Size:</b>                                   | 0.138 Inches  |
| <b>Material:</b>  | Iron Alloy 660 Overall                              |
| <b>Material Document And Classification:</b>                  | Ams 5525 Assn Std Single Material Response Overall  |
| <b>Precious Material And Location:</b>                        | External Surfaces Silver                            |
| <b>Precious Material:</b>                                     | Silver  |
| <b>Surface Treatment:</b>                                     | Silver Overall                                      |
| <b>Surface Treatment Document And Classification:</b>         | Ams 2410 Assn Std Single Treatment Response Overall |

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS698C06M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.