

Description

Thread Size: 5/32", Nut Length: 31/64", Nut Height: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS698C08M
Minimum Qty (MOQ):	25 EA
NSN:	5310-00-763-7886
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS698C08M Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.497 Inches Maximum
Nut Height:	0.450 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.229 Inches Minimum And 0.239 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Surface Treatment Document And Classification:	Ams 2410 Assn Std Single Treatment Response Overall

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698C08M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.