

Description

Thread Size: 1/4", Nut Length: 5/8", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS698C4 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5310-00-764-0042 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N NAS698C4 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.603 Inches Maximum |
| Nut Height: | 0.281 Inches Maximum |
| Plate Thickness: | 0.055 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.276 Inches Minimum And 0.286 Inches Maximum |
| Temp Rating: | 800.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 49.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall |
| Precious Material: | Silver |
| Surface Treatment: | Silver Overall |
| Surface Treatment Document And Classification: | Ams 2410 Assn Std Single Treatment Response Overall |

How to Order

Order this self locking-plate nut from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS698C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.