

Description

Thread Size: 19/64", Nut Length: 3/4", Nut Height: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS698C5M                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5310-01-011-2198                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS698C5M Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>                                      | Right-hand  |
| <b>Locking Feature:</b>                                       | Prevailing Torque All Metal Design  |
| <b>Lubrication:</b>   | Dry Film Lubricant  |
| <b>Mounting Hole Diameter:</b>                                | 0.130 Inches Minimum And 0.135 Inches Maximum   |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.757 Inches Maximum  |
| <b>Nut Height:</b>  | 0.328 Inches Maximum  |
| <b>Plate Thickness:</b>                                       | 0.065 Inches Maximum  |
| <b>Nut Mounting Provision:</b>                                | Straight Holes  |
| <b>Mounting Hole Arrangement Style:</b>                       | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b> | 0.354 Inches Minimum And 0.364 Inches Maximum   |
| <b>Temp Rating:</b>   | 450.0 Deg Fahrenheit Nominal  |
| <b>Thread Series:</b>   | Unjf  |
| <b>Thread Quantity Per Inch:</b>                              | 24  |
| <b>Nominal Thread Size:</b>                                   | 0.312 Inches  |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                  | Ms 5525 Assn Std Single Material Response Overall Or Ams 5535 Assn Std 2nd Material Response Overall Or Ams 5537 Assn Std 3rd Material Response Overall |

## How to Order

Order this plate - corner locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/NAS698C5M> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.