

**Description**

Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS7026H10                                  |
| Minimum Qty (MOQ):      | 20 EA                                       |
| NSN:                    | 5320-01-126-1278                            |
| Schedule B:             | 7318.24.0000                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS7026H10 Specifications

|   |   |
|---|---|
| <b>Head Style:</b>                                    | Flush Countersunk   |
| <b>Shank Diameter:</b>                                | 0.1880 Inches Minimum And 0.1895 Inches Maximum   |
| <b>Shank Style:</b>                                   | Pin-rivet, Multiple Grooved   |
| <b>Head Major Diameter:</b>                           | 0.332 Inches Maximum  |
| <b>Lubrication:</b>                                   | Cetyl Alcohol   |
| <b>Grip Length:</b>                                   | 0.563 Inches Minimum And 0.625 Inches Maximum   |
| <b>Features Provided:</b>                             | Casehardened And Sealant Vent Groove  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| <b>Shear Strength:</b>                                | 108000 Single Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| <b>Material:</b>                                      | Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Aisi Assn Std Single Material Response Overall  |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall                                |
| <b>Specification/standard Data:</b>                   | 80205-nas7026 Professional/industrial Association Standard  |

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7026H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.