

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7034H04
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-198-6514
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS7034H04 Specifications

Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.065 Inches Maximum
Shank Diameter:	0.1235 Inches Minimum And 0.1250 Inches Maximum
Head Major Diameter:	0.177 Inches Minimum And 0.193 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.189 Inches Minimum And 0.250 Inches Maximum
Features Provided:	Casehardened
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	108000 Single Pounds Per Square Inch
Special Features:	Sealant Escape Groove
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Astm A547 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7034 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7034H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.