

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7034H05
Minimum Qty (MOQ):	40 EA
NSN:	5320-01-366-1228
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS7034H05 Specifications

Head Style:	Err-090
Head Height:	0.059 Inches Minimum And 0.065 Inches Maximum
Shank Diameter:	0.1235 Inches Minimum And 0.1250 Inches Maximum
Shank Style:	Pin-riquet, Multiple Grooved
Head Major Diameter:	0.177 Inches Minimum And 0.193 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.251 Inches Minimum And 0.312 Inches Maximum
Features Provided:	Sealant Vent Groove
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi 8740 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7034 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7034H05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.