

**Description**

Pin part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7035H02
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-056-7278
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS7035H02 Specifications

<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.070 Inches Minimum And 0.077 Inches Maximum
<b>Shank Diameter:</b>	0.1550 Inches Minimum And 0.1565 Inches Maximum
<b>Head Major Diameter:</b>	0.219 Inches Minimum And 0.238 Inches Maximum
<b>Grip Length:</b>	0.063 Inches Minimum And 0.125 Inches Maximum
<b>Features Provided:</b>	Casehardened
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Special Features:</b>	Cetyl Alcohol Lubrication,sealant Escape Groove
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas7035 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7035H02> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.