

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS7036H04 |
| Minimum Qty (MOQ): | 20 EA |
| NSN: | 5320-01-105-9431 |
| Schedule B: | 7318.24.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS7036H04 Specifications

| | |
|---|---|
| Head Style: | Err-090 |
| Head Height: | 0.079 Inches Minimum And 0.086 Inches Maximum |
| Shank Diameter: | 0.1880 Inches Minimum And 0.1895 Inches Maximum |
| Shank Style: | Pin-rivet, Multiple Grooved |
| Head Major Diameter: | 0.268 Inches Minimum And 0.288 Inches Maximum |
| Lubrication: | Cetyl Alcohol |
| Grip Length: | 0.189 Inches Minimum And 0.250 Inches Maximum |
| Features Provided: | Casehardened |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Hardness Rating: | 78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall |
| Shear Strength: | 108000 Single Pounds Per Square Inch |
| Material: | Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas7036 Professional/industrial Association Standard |

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7036H04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.