

Description

Fastener Length: 2-5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7038H05
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-383-0025
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS7038H05 Specifications

Fastener Length:	2.1200 Inches Minimum And 2.3200 Inches Maximum
Head Style:	Err-090
Head Height:	0.1040 Inches Minimum And 0.1110 Inches Maximum
Shank Diameter:	0.2480 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.3540 Inches Minimum And 0.3800 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.2510 Inches Minimum And 0.3120 Inches Maximum
Features Provided:	Sealant Vent Groove
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi 8740 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.