

**Description**

Fastener Length: 2-5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7038H05
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-383-0025
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS7038H05 Specifications

<b>Fastener Length:</b>	2.1200 Inches Minimum And 2.3200 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.1040 Inches Minimum And 0.1110 Inches Maximum
<b>Shank Diameter:</b>	0.2480 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.3540 Inches Minimum And 0.3800 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.2510 Inches Minimum And 0.3120 Inches Maximum
<b>Features Provided:</b>	Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	108000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Aisi 8740 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.