

P/N NAS7038H07

Description

Fastener Length: 2.37", NAS7038 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

National Motor Freight:

SKU / Model:	NAS/038H0/
Minimum Qty (MOQ):	10
NSN:	5320-01-382-8121
Schedule B:	7318.24.0000
ECCN:	FARQO

096320, Rivets I / S Nickel Plated Buffed



^{*} See page 2 for technical characteristics

P/N NAS7038H07 Specifications

Fastener Length:	2.370 Inches Nominal
Head Style:	Err-090
Head Height:	0.104 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.250 Inches Nominal
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.354 Inches Minimum And 0.380 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Features Provided:	Sealant Vent Groove
Minimum Tensile Strength:	2500 Pounds Per Square Inch
Shear Strength:	10600 Double Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi 8740 Assn Std Single Material Response Overall
Surface Treatment:	Chromate Overall And Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7038 Professional/industrial Association Standard

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/NAS7038H07 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.