

**Description**

Fastener Length: 2-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS7038H10
Minimum Qty (MOQ):	15 EA
NSN:	5320-01-382-7411
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS7038H10 Specifications

<b>Fastener Length:</b>	2.750 Inches Nominal
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.104 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.250 Inches Nominal
<b>Head Major Diameter:</b>	0.354 Inches Minimum And 0.380 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.563 Inches Minimum And 0.625 Inches Maximum
<b>Features Provided:</b>	Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	2500 Pounds Per Square Inch
<b>Shear Strength:</b>	10600 Double Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Aisi 8740 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall And Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas7038 Professional/industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.