

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7038H11
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-086-3599
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS7038H11 Specifications

Head Style:	Err-090
Head Height:	0.104 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.2480 Inches Minimum And 0.2495 Inches Maximum
Head Major Diameter:	0.354 Inches Minimum And 0.380 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.626 Inches Minimum And 0.688 Inches Maximum
Features Provided:	Casehardened And Sealant Vent Groove
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7038 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.