

Description

Fastener Length: 3-9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7038H15
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-454-6871
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS7038H15 Specifications

Fastener Length:	3.370 Inches Minimum And 3.570 Inches Maximum
Head Style:	Err-090
Head Height:	0.104 Inches Minimum And 0.111 Inches Maximum
Shank Diameter:	0.2480 Inches Minimum And 0.2495 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.354 Inches Minimum And 0.380 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.933 Inches Minimum And 0.939 Inches Maximum
Features Provided:	Casehardened And Sealant Vent Groove
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7038 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.