

**Description**

Fastener Length: 3-9/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7038H15
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-454-6871
Schedule B:	7318.24.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS7038H15 Specifications

<b>Fastener Length:</b>	3.370 Inches Minimum And 3.570 Inches Maximum
<b>Head Style:</b>	Err-090
<b>Head Height:</b>	0.104 Inches Minimum And 0.111 Inches Maximum
<b>Shank Diameter:</b>	0.2480 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Style:</b>	Pin-rivet, Multiple Grooved
<b>Head Major Diameter:</b>	0.354 Inches Minimum And 0.380 Inches Maximum
<b>Lubrication:</b>	Cetyl Alcohol
<b>Grip Length:</b>	0.933 Inches Minimum And 0.939 Inches Maximum
<b>Features Provided:</b>	Casehardened And Sealant Vent Groove
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Hardness Rating:</b>	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
<b>Shear Strength:</b>	108000 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Aisi Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas7038 Professional/Industrial Association Standard

## How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7038H15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.