

Description

Pin part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7040H06
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-219-7264
Schedule B:	7318.24.0000
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS7040H06 Specifications

Head Style:	Err-090
Head Height:	0.130 Inches Minimum And 0.137 Inches Maximum
Shank Diameter:	0.3105 Inches Minimum And 0.3120 Inches Maximum
Shank Style:	Pin-rivet, Multiple Grooved
Head Major Diameter:	0.443 Inches Minimum And 0.475 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	78.0 Rockwell Superficial 15-n Minimum Overall And 82.0 Rockwell Superficial 15-n Maximum Overall
Shear Strength:	108000 Single Pounds Per Square Inch
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Aisi Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas7040 Professional/industrial Association Standard

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7040H06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.