

P/N NAS7104-12

Description

Fastener Length: 1-3/16", Thread: 10-32, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS710412
Minimum Qty (MOQ): 95 EA

NSN: 5305-01-436-1734

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N NAS7104-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.160 Inches Minimum And 1.190 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.456 Inches Minimum And 0.508 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas7104 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS7104-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.