

**Description**

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                               |
|-------------------------|-------------------------------|
| SKU / Model:            | NAS71048                      |
| Minimum Qty (MOQ):      | 40 EA                         |
| NSN:                    | 5305-01-436-0270              |
| Schedule B:             | 7318.15.8085                  |
| ECCN:                   | 9A991                         |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE  
AVAILABLE

## P/N NAS7104-8 Specifications

|                                                       |                                                                                                                |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                             |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                     |
| <b>Thread Length:</b>                                 | 0.425 Inches Nominal                                                                                           |
| <b>Fastener Length:</b>                               | 0.910 Inches Minimum And 0.940 Inches Maximum                                                                  |
| <b>Head Style:</b>                                    | Flat Countersunk                                                                                               |
| <b>Head Diameter:</b>                                 | 0.456 Inches Minimum And 0.508 Inches Maximum                                                                  |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum                                                                |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1                                                                                            |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches                                                                                                   |
| <b>Grip Length:</b>                                   | 0.490 Inches Minimum And 0.510 Inches Maximum                                                                  |
| <b>Thread Quantity Per Inch:</b>                      | 28                                                                                                             |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                                                                  |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                 |
| <b>Material:</b>                                      | Steel Comp 4340 Overall And Steel Comp 8740 Overall                                                            |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049gca-6322 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                                                           |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Ty2 Cl2 Fed Spec Single Treatment Response Overall                                                   |
| <b>Thread Series Designator:</b>                      | Unjf                                                                                                           |
| <b>Specification/standard Data:</b>                   | 80205-nas7104-8 Professional/Industrial Association Standard                                                   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7104-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.