

Description

length: 0.678", grip: 0.312", thread: 10-32, 100°, flush head close tolerance bolt - corrosion resistant steel - philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS72035
Minimum Qty (MOQ):	50
NSN:	5305-01-269-5881
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS7203-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	0.663 Inches Minimum And 0.693 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1879 Inches Minimum And 0.1887 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7203-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.