

**Description**

length: 0.740", grip: 0.375", thread: 10-32, 100°, flush head close tolerance bolt - corrosion resistant steel - philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS72036
Minimum Qty (MOQ):	50
NSN:	5305-01-504-2726

NO IMAGE  
AVAILABLE

## P/N NAS7203-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.365 Inches Nominal
<b>Fastener Length:</b>	0.740 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.381 Inches Nominal
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.1900 Inches
<b>Grip Length:</b>	0.375 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std 1st Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7203-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.