

P/N NAS7203A11

Description

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS7203A11

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-533-4892

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS7203A11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.365 Inches Nominal
Fastener Length:	1.038 Inches Minimum And 1.068 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.187 Inches Minimum And 0.188 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
End Item Identification:	C-135 Aircraft
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt,100degree Head, Cruciform Recess,close Tolerance
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas4006 National Std/spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS7203A11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.