



★ FASTENERS

Military-Fasteners.com

P/N NAS7203A6

## Description

length: 0.74", grip: 0.375", thread: 10-32, flush head, close tolerance, aluminum coated corrosion resistant steel, philips recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS7203A6
Minimum Qty (MOQ):	10
NSN:	5305-01-267-9917
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS7203A6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.365 Inches Nominal
<b>Fastener Length:</b>	0.725 Inches Minimum And 0.755 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Grip Diameter:</b>	0.1879 Inches Minimum And 0.1887 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type Ii
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 11,cl 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7203A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.